

XGS46J

MOBILE ELEVATING WORK PLATFORM

Comply with ANSI/CSA



XGS46J

FEATURES

MEASUREMENTS

16 m (53') working height Without Limited:272 kg (600 lb) capacity

PRODUCTIVITY

1.83 m x 0.76 m (6' x 2' 6") steel platform 4WD

Solid tire

Self-leveling platform

Hydraulic platform rotation

Fully proportional controls

Drive enable

Horn

Hour meter

Tilt alarm

Lift and lower alarm

360° continuous turntable rotation

Lockable turntable covers

Zero tailswing

Engine gauge package

Alarm package

Dual flashing beacons

POWER

Kubota

2700 rpm/36.8 kW

Deutz

2600 rpm/36.4 kW


HIGHLIGHT


- Multi-directional precise positioning up, down and across functions as well as excellent stretch functions.
- Electrical system adopts a distributed PLC control technology, adaptive proportional valve control method, make the product environment adaptability with lead.
- 360° continuous turntable rotation.
- Compact and flexible, convenient for container transportation.


OPTIONS

Power supply to platform Compressed air line to platform Anti-impact bracket for platform Rough terrain foam-filled tires









MAIN PARAMETER

Item	Metric	Imperial
Overall dimensions (stowed)	9.4 m×2.32 m×2.48 m	31 ft \times 7 ft 7 in \times 8 ft 1 in
Overall dimensions (transportation)	9.1 m×2.32 m×2.48 m	29 ft 10 in × 7ft 7 in × 8 ft 1 in
Platform size	1.83 m×0.76 m×1.15 m	$6 \text{ ft} \times 2 \text{ ft } 6 \text{ in} \times 3 \text{ ft } 9 \text{ in}$
Wheelbase	2.36 m	7 ft 9 in
Minimum ground clearance(center)	300 mm	11.81 in
Maximum working height	16 m	53 ft
Maximum platform height	14 m	46 ft
Maximum working range	12.7 m	42 ft
Lift capacity	272 kg; 272 kg/350 kg(option)	600 lb; 600 lb/772 lb(option)
Boom luffing range	-14°~73°	-14°~73°
Jib luffing range	-65°~70°	-65°~70°
Turntable rotation	360°continuous rotation	360°continuous rotation
Platform rotation	160°	160°
Tailswing	1.12 m	3 ft 8 in
Maximum drive speed	6 km/h	3.73 mph
Minimum turning radius(outside)	4.7 m	15 ft 5 in
Weight	8050 kg	17747 lb
Gradeability	45%	45%
Engine type	Kubota/Deutz	Kubota/Deutz
Engine rated power	36.8 kW/2700 rpm; 36.4 kW/2600 rpm	49.3 hp/2700 rpm; 48.8 hp/2600 rpm
Tires	32×12-20/7.5	32×12-20/7.5